

Slim • Portable • Stylish



10D

- Intel® Centrino™ mobile technology
 - Intel® Pentium® M processor ULV (2MB L2 Cache, 400MHz FSB)
 - Intel® Pro/Wireless 2200BG (802.11b/g) network connection
- Genuine Windows® XP Professional Edition
- Clear, sharp 10.6-inch WXGA TFT LCD screen
- Integrated 4 in 1 media card reader
- Instant-on multimedia applications
- Slim, lightweight design - Weights only 1.47Kg
- Runs on battery power for up to five hours
- Choice of high fashion colors: burgundy or ocean blue



10D

System Specifications

Processor	Intel® Ultra Low Voltage CPU Intel® Pentium® M processor ULV 733 and higher (FSB 400MHz) 2MB L2 Cache Intel® Celeron® M processor ULV 353 and higher (FSB 400MHz) 512KB~1MB L2 Cache
Chipset	North Bridge: Intel® 855GME South Bridge: Intel® ICH4-M
System Memory	Two DDR 266 SODIMM Slots each for 256/512/1024MB (Max. 2GB)
Hard Disk Drive	2.5" 9.5mm high Hard Disk Drive, 40/60/80GB Ultra DMA 100 and S.M.A.R.T.
Optical Media Device	Internal Combo Drive (DVD/CD-RW) or DVD Dual (DVD-R/CD-RW/DVD-RW/DVD+RW)
Display	10.6" TFT LCD with WXGA resolution
Graphics & Video	Integrated in core logic Intel® enhancement AGP BUS equivalent hardware 2D/3D video graphic accelerators Intel® Dynamic system shared memory up to 64MB
Audio	Embedded PCI Bus 16-bit Compliant with AC-97 Two 1W Speakers with chamber
I/O Devices	One Type II PCMCIA slot 4 in 1 media card reader support MS/MS Pro/SD/MMC
I/O Ports	Two USB2.0 connectors One IEEE 1394 port One 15 pins D-Sub connectors for external monitor One Line-Out phone jack for external speakers One Mic-In phone jack for external microphone One RJ-11 jack for internal 56Kbps V.90 modem One RJ-45 jack for internal 10/100Mbps Ethernet One DC-In jack
Keyboard	87 (US) Keys with Windows Key Function Keys: Fn+F3: LCD Off/On Toggle Fn+F4: Suspend mode Fn+F5: LCD/CRT Display Switch Fn+F6: LCD Brightness Decrease Fn+F7: LCD Brightness Increase Fn+F8: Volume Down Fn+F9: Volume Up Fn+F10: Mute
Wireless/Communications	Modem: Internal 56K V.90 Fax/Modem Ethernet: Integrated 10/100Mbps Ethernet Wireless: Mini PCI WLAN module 802.11 b/g
AC Adapter	Input: AC 100~240V 50/60Hz, Output: 20V/3.0A/60W
Battery	Standard: 6 cells 2000mAh Li-Ion battery (Approx. 5hrs)
Dimensions & Weight	266mm (W) X 202.5mm (D) X 29.5~34.5mm (H) 1.47Kg/3.23lbs
Certification	FCC, CUL, CE
Security	Kensington Lock / Administrator password / Boot password



The specification and pictures are subject to change without notice.
All brand names are registered trademarks of their respective owners.



Taipei (Headquarters)
Twinhead International Corporation
10F, 550, Rueiguang Road,
Neihu, Taipei, 114, Taiwan, R.O.C.
Tel : 886-2-5589-9999
Fax: 886-2-5555-7777
<http://www.twinhead.com>

U.S.A.
Twinhead Corporation
48303 Fremont Blvd.
Fremont, CA94538, U.S.A.
Tel : 1-510-492-0828
Fax: 1-510-492-0820

China
Beijing Twinhead Technology Ltd.
Room208, Haowei Building, No.25,
BeiTaiPingZhuang Road, HaiDianDistrict,
Beijing, China, 100088
Tel : (86) 10 62381203
Fax: (86) 10 62381205

Germany
Twinhead GmbH.
Nikolaus-Otto-Strasse 4
40670 Meerbusch-Osterath
Germany
Tel : 49-2159-6944-0
Fax: 49-2159-6944-20